

Wall luminaires · surface washers

Housing: One piece, die cast aluminum housing with adjustable die cast arm and mounting canopy. Fixture tilt angle is adjustable from -30° to 90° in steps of 10°. The mounting canopy is supplied with a round, die cast aluminum rotational plate which allows the housing to be precisely leveled or rotated after installation. Mounting plate attaches directly to a standard 4" octagonal wiring box. Can be mounted in upward facing orientation. Die castings are marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy.

Enclosure: Clear tempered glass with a machined step to provide a flush finish with the door frame. Reflector is anodized aluminum with an optically textured glass insert to provide an even distribution of light from the LED source. The door frame is die cast aluminum with mechanically captive, stainless steel screws threaded into stainless steel inserts. The door is tethered to the housing with two safety cables. One piece, molded silicone gasket for use in wet locations mounted in any orientation.

Electrical: 40W LED luminaire, 44.7 total system watts, -30° C start temperature. Integral 120V through 277 V electronic LED driver, 0-10V dimming. LED module(s) are available from factory for easy replacement. Standard LED color temperature is 4000K with a >80 CRI. Available in 3000K (>80 CRI); add suffix K3 to order.

Note: Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to www.bega-us.com.


Finish: All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

UL listed for US and Canadian Standards, suitable for wet locations.
Protection class: IP65.

Weight: 11 lbs.

Luminaire Lumens: 2039

Tested in accordance with LM-79-08



Lamp	A	B	C
6854 LED 40 W LED	8 ⁷ / ₈	4	19 ¹ / ₄

Type:
BEGA Product:
Project:
Voltage:
Color:
Options:
Modified:

